

OWNER'S MANUAL SUPPLEMENT
2002 600 CLASSIC EDGE
PN 9916731



IMPORTANT: This is a supplement to your owner's manual. This information should remain with your owner's manual at all times.

Capacities and Dimensions	
Body Style	Edge
Rider Capacity	1
Coolant Capacity (qts)	4
Chaincase Oil Capacity (oz.)	11
DryWeight (Est.)	512
Fuel Tank capacity (Gallons)	11.8
Gearcase Oil Capacity (oz.)	n/a
Height (in.)	48
Length (in.)	113
Oil Capacity (Quarts)	4
Ski Center Distance (in.)	42.5
Width (in.)	48
Brake Type	Hydraulic
Drive Clutch Center Distance	11.5
Clutch Type	P-85
Track Length	121
Track Width	15
Drive Chain Length	74
Reverse Transmission	Standard
Sprocket Ratio	23:39
Features	
Electric Fuel Gauge	Standard
Electric Start	Standard
Low Oil Light	Standard
Parking Brake	Standard
Speedometer	Std 5 Inch, White Face
Tachometer	Std
Wear Strips	Std
Easy Throttle	N/A
Hood Color	Sonic Blue

Engine and Cooling	
Engine Model Number	S2097-6044PL6E
Alternator Output	280 Watts
Bore x Stroke (mm)	77.25x64
Displacement	593
Carburetor/Throttle Body	1 Mikuni
Carburetor Model	TM38
Main Jet	430
Pilot Jet	40
Jet Needle / Clip Position	9DFH7-60-3 /
Needle Jet	P8
Cutaway	2.5
Fuel Screw	1.75
Idle RPM +/-200	1400
Cooling	Liquid
Cylinders	2
Ignition Timing °BTDC @ RPM	24° @ 3000 - 3500
Ignition Type	Digital
Oil Injection	VES
Spark Plug	Champion RN57YCC
Suspension	
Front Type	Edge
IFS Shock Type	Sel
Rear Type	M-10
Front Track Shock	Fox IFP
Rear Track Shock	Fox IFP w/Res

Carburetor Jetting

Clutching Chart

	AMBIENT TEMPERATURE	Below -30°F Below -34°C	-30° to -10°F -34° to -23°C	-10° to +10°F -23° to -12°C	+10° to +30°F -12° to -1°C	+30° to +50°F -1° to +10°C	Above +50°F Above +10°C	Altitude Meters (Feet)	Shift Weight	Drive Clutch Spring	Driven Clutch Spring	Driven Helix	Chaincase Geariang
Altitude Meters (Feet)	0-600 (0-2000)	460 #4	440 #3	420 #3	400 #3	390 #3	370 #2	0-900 (0-3000)	10-58	Dk Blue White	Silver/Blue #2	R11	23:39:74
	600-1200 (2000-4000)	430 #3	410 #3	400 #3	380 #3	360 #2	350 #2	900-1800 (3000-6000)	10-56	Dk Blue White	Silver/Blue #2	R11	23:39:74
	1200-1800 (4000-6000)	400 #3	390 #3	370 #3	350 #2	340 #2	320 #2	1800-2700 (6000-9000)	10-54	Dk Blue White	Silver/Blue #2	R11	23:39:74
	1800-2400 (6000-8000)	380 #3	360 #3	350 #2	330 #2	310 #2	290 #2	2700-3700 (9000-12000)	10-54	Dk Blue White	Silver/Blue #3	R11	23:39:74
	2400-3000 (8000-10000)	350 #3	340 #2	320 #2	300 #2	290 #2	270 #2						
	3000-3600 (10000-12000)	330 #2	310 #2	290 #2	280 #2	260 #2	240 #2						

PN 9916731 Rev 02 3/01

Printed in U.S.A.

